



W26000^{SERIES} 6" and 8" Diameter Up / Down Light Wall Mount Aluminum Cylinder

Specifications

Cylinder

.080" Aluminum, rolled and seam welded. See finish note.

Cylinder Aperture Top

Cast aluminum with 3/16" thick clear tempered glass caulked to frame.

Cylinder Aperture Bottom

Open aperture standard, one-piece aluminum mini-groove baffle or louver guard painted matte black available. See options and accessories. Metal halide fixtures provided with tempered clear glass shield and safety chain.

Reflector

Spun aluminum electro-chemically processed to provide semi-specular finish.

Ballast

Prewired HX-H.P.F. core and coil with capacitor and starter.

Lamp

Phosphor coated (by others).

Lamp Holder

High heat porcelain socket 4KV rated w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket. See table.

Mounting Plate

Galvanized plate bolts directly to outlet box. Supports ballast assemblies and fits into wall bracket.

Wall Bracket

Ballast housing cover is aluminum construction, seam welded. Bolts to ballast mounting plate and supports cylinder. Finished same as cylinder.

Finish

Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electro-static applied and baked. Standard colors black, white and bronze. Custom colors are available. Consult factory or sales representative.

Labels

U/L, CU/L listed & I.B.E.W labeled; suitable for wet location.

Photometric Information

Contact factory or visit www.escolighting.com



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

3254 North Kilbourn Avenue Chicago, Illinois 60641
Phone 773-427-7000 Fax 800-217-1260 www.escolighting.com



W26000^{SERIES}
6" and 8" Diameter
Up / Down Light
Wall Mount Aluminum Cylinder

Wall Mount Up / Down Light				
Catalog Number Standard Lamp / Open Rated Lamp	Watts	Diameter	Light Source	Lamp Base
W26011	35	6"	HPS	Medium
W26012	50	6"	HPS	Medium
W26013	70	6"	HPS	Medium
W26022* / WO26022	50	6"	MH	Medium
W26023* / WO26023	70	6"	MH	Medium
W26023PAR	70	6"	MH PAR38	Medium
W26014	100	8"	HPS	Medium
W26015	150	8"	HPS	Medium
W26024* / WO26024	100	8"	MH	Medium
W26024PAR	100	8"	MH PAR38	Medium

* Includes clear tempered glass lens and safety chain regressed in aperture.

Color
Suffix Catalog
Number With

W= White
BZ= Bronze
BL= Black


Voltage
Suffix Catalog
Number With

1= 120V
2= 208V
3= 240V
4= 277V
5= 480V
8= Multi-tap wired
for 277V.
9= Multi-tap
unwired.
0= 347V

Options & Accessories



Mini-groove black baffle.
Replace 260 in catalog
number with 261.



Louver guard option.
Suffix catalog number
with LG2.



Photo
Control
Option
Suffix
Catalog #
With

PC4 120 Volt
PC5 208-277 Volt



Fuse and Fuse Holder
Suffix Catalog
Number With "F"



Electronic metal halide ballast option.
Suffix catalog number with "E".
Metal halide 8" dia. only.



Mini cast aluminum wall mount
option for 8"
diameter electronic
metal halide bal-
last only.

Suffix Catalog # With	Quartz Re-strike Systems
E1A	Mini-Can Socket assembly for separate circuit entry with relay for one lamp burning only.
E2	Emergency re-strike system, mini-can socket assembly (100 watt maximum lamp).
E65	Emergency re-strike system, mini-can socket assembly (100 watt maximum lamp) with time delay.



Dimensional Information

