



606^{SERIES}
6" Diameter Compact Fluorescent
Aluminum Cylinder
Surface, Pendant, Wall or Trunion Mount

Specifications

Cylinder

.080" Aluminum. See finish note.

Reflector

Spun aluminum alloy 3002, electro-chemically processed to provide specular finish.

Reflector Top

Extruded aluminum, supports socket and reflector. Dissipates heat from lamp and socket.

Ballast

High power factor, electronic, 120V—277V class P ballast.

Lamp

Compact fluorescent by others.

Mounting Pan (Surface Mount)

Cast aluminum for direct surface mount over electrical box. See finish note.

Mounting Strap (Surface Mount)

Galvanized steel, mounts directly to outlet box. Supports pan with 1/4-20 studs and wing nuts.

Canopy / Stem Set (Pendant Mount)

0-45° hang straight for 3/8" I.P. See finish note.

Wall Bracket (Wall Mount)

One-piece cast aluminum bracket/arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness. See finish note.

Trunion Mount

14 Gauge (.074") steel trunion with 180° pivot, adjusting knobs lock fixture into position. Designed for direct mounting to electrical box. See finish note.

Mounting Pan (Trunion Mount)

Cast aluminum with center opening for input leads. See finish note.

Finish

Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electro-static applied and baked. Standard colors black, white and bronze. Custom colors are available. Consult factory or sales representative.

Labels

U/L, CU/L listed & I.B.E.W labeled; flush, pendant and trunion mount suitable for wet location for under canopy mounting, wet location for wall mount.

Photometric Information

Contact factory or sales representative.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



3254 North Kilbourn Avenue Chicago, Illinois 60641
Phone 773-427-7000 Fax 800-217-1260 www.escolighting.com





Surface Mount

Catalog Number	Watts	Lamp Base	Color Suffix Catalog Number With
S606D1	PL13W	G24q-1	W= White
S606D2	PL18W	G24q-2	BZ= Bronze
S606D3	PL26W	G24q-3	BL= Black
S606T2	PLT18W	GX24q-2	
S606T3	PLT26W	GX24q-3	
S606T4	PLT32W	GX24q-3	

Options & Accessories



Trunion mount
Change S in catalog number to T.




Pendant mount
Suffix catalog number with Pxx. xx= Stem length in inches.



Cast aluminum wall mount. Change S in catalog number to W.



Mini-groove black baffle.
Replace 60 in catalog number with 61.



Louver guard option.
Suffix catalog number with LG1.



Fuse and Fuse Holder
Suffix Catalog Number With "F"

Dimensional Information

