



SPECIFICATIONS

Cylinder: Extruded aluminum 6063-T5, .090" thick.* See finish note.

Reflector: Spun aluminum alloy 3002, electro-chemically processed to provide specular finish.

Ballast Prewired C.W.A., H.P.F. core and coil with capacitor and starter for HPS.

Lamp Phosphor coated medium base (by others).

Lamp Holder High heat porcelain, 4 KV rated with nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Canopy Set: (Pendant Mount) 0-45° hang straight for 3/8" x 12" long steel pipe standard length with P2 accessory. Other lengths available. Finished to match housing.*



Surface Mount: Cast Aluminum 5/32" thick EZ5® splice box mounts to standard 4" octagonal junction box. Safety clip supports cylinder for hands free splice connection. Three #10-32 screws set 120° apart for twist and lock-up of cylinder to splice box. Supplied with quick-connect wiring harness. EZ5® design allows the contractor to install the fixture in 5 easy minutes or less. See illustration above. Finished same as housing. See finish note.

Wall Bracket Assembly: One-piece cast aluminum bracket /arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness. Escos EZ5® Mounting System allows the contractor to install the fixture in 5 minutes or less. Finished same as housing. See finish note.

Trunion Mount: 14 Gauge (.074") steel trunion with 180° pivot, adjusting knobs lock fixture into position. Designed for direct mounting to electrical box. See finish note.

Finish: Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electro-static applied and baked. Standard colors white or bronze. Custom colors are available. Consult factory or sales representative.

Labels: Pendant mount suitable for damp location; wall mount suitable for wet location; surface mount suitable for wet location under covered ceiling. ETL, CETL and I.B.E.W. labeled.


Fixture Warranty: The fixture mechanics are guaranteed to be free from defective material and workmanship, under normal installation and operating conditions, for **ten years** from date of shipment from the factory. See General Terms and Conditions.

Photometric Information: Contact factory.

*Canopy set for indoor applications only; contact factory for other applications and designs.
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



DIMENSIONS












HOW TO ORDER

Catalog Number Standard Lamp / Open Rated Lamp	Watts	Light Source	Lamp Base	Color Suffix Catalog Number With	Voltage Suffix Catalog Number With
SX6011	35	HPS	Medium	White= W	120V= 1
SX6012	50	HPS	Medium	Bronze= BZ	208V= 2
SX6013	70	HPS	Medium	Black= BL	240V= 3
SX6021PAR	35/39	MH	Medium		277V= 4
SX6022* / SXO6022	50	MH	Medium		Multi-tap wired for 277V.= 8
SX6023* / SXO6023	70	MH	Medium		Multi-tap unwired.= 9
SX6023PAR	70	MH	Medium		347V= 0
* Includes clear tempered glass lens regressed in aperture.					

EXAMPLE: SX61006BLFP224 = 6" diameter cylinder, mini-groove black baffle, fuse and fuse holder, pendant mount with 24" stem, textured black

Aperture Accessories	
	Mini-Groove Black Baffle Replace 60 in catalog number with 61 Example: SX6000 becomes SX6100
	Louver Guard Suffix catalog number with LG1 Example: SX6000 becomes SX6000LG1
Mounting Options	
	Trunion mount Change S in catalog number to T Example: SX6000 becomes TX6000
	Pendant Mount Suffix P2=12" long stem (standard) P2X="X" is custom stem length Example: P224= 24" long stem
	EZ5® Wall Mount Change Prefix S to W Example: SX6000 becomes WX6000
Other	
	Photo Control Suffix Catalog number with 120 Volt = PC4 208-277 Volt = PC5 Example: SX6000 becomes SX6000PC5
	Fuse and Fuse Holder Suffix Catalog Number With F Example: SX6000 becomes SX6000F



3254 North Kilbourn Avenue Chicago, Illinois 60641-4505
 Phone: 773-427-7000 Fax: 800-217-1260 www.escolighting.com
A Woman-Owned Business
 Established 1975

