

SPECIFICATIONS

Housing: Spun aluminum .090" thick. See Finish Note.

Reflector: Spun aluminum .040" thick, finished bright anodized.

Ballast: H.I.D.: prewired C.W.A., H.P.F. core and coil with capacitor and starter for HPS. Fluorescent: electronic with super lamp guard circuitry.

Lamp: Clear or phosphor coated H.I.D. medium base or compact fluorescent (by others).

Lamp Holder: H.I.D.: high heat porcelain w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Fluorescent: compact fluorescent base (see ordering information).

Door Frame: Spun aluminum ring, gasketed retains lens. Torsion spring lock-up with safety chain.

Lens: Corning #73 prismatic tempered glass.

Cross Bar: 4" Long, tapped 3/8" I.P.S. galvanized steel. Surface mount only.

Quick Connect Box: 16 Gauge (.059") galvanized steel finished to match housing. See finish note.

Pendant Mount: 0-45° hang straight for 3/8" x 12" long steel pipe standard length with P2 accessory. Finished to match housing.**

Wall Bracket Assembly: One-piece cast aluminum bracket/arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness. Escos's **EZ5 Mounting System** allows the contractor to install the fixture in 5 minutes or less. Finished same as housing. See finish note.

Finish: All painted parts are washed in alkaline solution, rinsed in an iron phosphate, baked dry, then painted with a TGIC polyester powder coating electrostatic applied and baked.

Labels: Surface and wall mount suitable for wet location; pendant mount suitable for damp location. ETL, CETL and I.B.E.W. labeled.

Photometric Information: Contact factory or visit www.escolighting.com.

**Canopy set for indoor applications only; contact factory for other applications and designs.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Surface Mount



Pendant Mount



Quick Connect
Splice Box



Wall Mount



3254 North Kilbourn Avenue Chicago, Illinois 60641-4505
 Phone: 773-427-7000 Fax: 800-217-1260 www.escolighting.com

A Woman-Owned Business
Established 1975



HOW TO ORDER

Use the table below to choose the 4500 series fixture of your choice. Select a number from each list that corresponds to a specific feature unique to your desired requirements.

EXAMPLE: S453T242BLP724-1 = Surface mount, 2-fluorescent PLT 42W lamps, textured black, pendant mount with 24" stem, 120V.

<p>S W 4 5 X X X -X</p>					
Mounting System	Light Source	Wattage H.I.D.	Wattage / Lamp Base Compact Fluorescent	Color	Voltage
S= Surface mount	1= High Pressure Sodium	2= 50W	D18= 1-18W / G24q-2	BZ= Textured Bronze	1= 120V
W= Wall mount	2= Metal Halide	3= 70W	D218= 2-18W / G24q-2	BL= Textured Black	2= 208V
	3= Compact Fluorescent	4= 100W	DL26= 1-26W / G24q-3	W= Sky White	3= 240V
			D226= 2-26W / G24q-3	SD= Silver	4= 277V
			T26= 1-26W / GX24q-3	Other Consult Factory	5= 480V
			T226= 2-26W / GX24q-3		8= Multi-Tap Prewired for 277V
			T32= 1-32W / GX24q-3		9= Multi-Tap Unsired
			T232= 2-32W / GX24q-3		0= 347V
			T42= 1-42W / GX24q-4		
			T242= 2-42W / GX24q-4		

Mounting Options
 Suffix catalog number with:

B= Quick connect splice box.

P7x= Pendant and canopy mount (x = required stem length in inches).

DIMENSIONS

