



Si60008^{Series}
8" Diameter Incandescent
Aluminum Cylinder
Surface, Pendant or Wall Mount

Specifications

Cylinder

.080" Aluminum, rolled and seam welded. See finish note.

Reflector

Spun aluminum #3002, polished to a mirror finish then electro-chemically processed to provide specular finish.

Lamp

Up to 250W PAR or 150W A21 lamps (by others).

Lamp Holder

High heat porcelain, 4 KV rated with nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Mounting Pan (Surface Mount)

Cast aluminum with 3/4" inner collar, finished to match cylinder housing.

Mounting Strap (Surface Mount)

Galvanized steel, mounts directly to outlet box. Supports pan with 1/4 x 20 studs and wing nuts. Flush style.

Canopy Set (Pendant Mount)

0-45° hang straight for 3/8" I.P. Stem finished to match housing.

EZ5 Wall Bracket (Wall Mount)

One-piece cast aluminum bracket/arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness.

Finish

Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electro-static applied and baked. Standard colors black, white and bronze. Custom colors are available. Consult factory or sales representative.

Labels

U/L, CU/L listed & I.B.E.W labeled; suitable for wet location under covered ceiling. Wall mount listed wet location.

Photometric Information

Contact factory.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



3254 North Kilbourn Avenue Chicago, Illinois 60641
Phone 773-427-7000 Fax 800-217-1260 www.escolighting.com



Surface Mount Incandescent Cylinder	
Catalog Number	Maximum Wattage
Si60008 Surface mount open aperture.	150W A21 or 250W PAR Lamp
Si61008 Surface mount open with baffle.	150W A21 or 250W PAR Lamp

Color Suffix Catalog Number With	
W=	White
BZ=	Bronze
BL=	Black


Options & Accessories



Pendant mount
Suffix catalog number with P2xx. xx= stem length in inches.



Mini-groove black baffle option.



Louver guard option. Suffix catalog number with LG2.



Cast aluminum wall mount. Change S in catalog number to W.



Fuse and Fuse Holder
Suffix Catalog Number With "F"




Photo Control Option
Suffix Catalog # With

PC4 120 Volt

Dimensional Information

